

SQA4N150

1500V 4A N-Channel Enhancement Mode Power MOSFET

Features

- Low on-Resistance: $R_{DS(on)}=3.6\Omega(\text{typ.})$
- Special Process Technology for high ESD Capability
- 100% Avalanche Test
- Good Stability and Uniformity with High E_{AS}



Description

The SQA4N150 is an N-Channel enhancement mode power MOSFET, it has low static on-resistance and high avalanche energy strength. This device provide excellent switching performance for switched mode power supplies, active power factor correction and electronic lamp ballasts.

Applications

- Switched Mode Power Supplies
- Active Power Factor Correction, Electronic Ballasts

Package Type & Internal Circuit



Absolute Maximum Ratings @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Ratings	Unit
V_{DSS}	Drain to Source Voltage	1500	V
V_{GSS}	Gate to Source Voltage	± 30	V
I_D	Drain Current	$T_C=25^\circ\text{C}$	4
		$T_C=100^\circ\text{C}$	2.5
I_{DM}	Pulsed Drain Current (Note1)	12	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	156
	Derate above 25°C	1	W/ $^\circ\text{C}$
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	600	mJ
T_J	Operating Junction Temperature Range	$-55\sim+150$	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	$-55\sim+150$	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	0.8	$^\circ\text{C/W}$
$R_{th(J-A)}$	Thermal Resistance, Junction to Ambient	62.5	$^\circ\text{C/W}$

**Electrical Characteristics** @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =1mA	1500	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	3.5	-	4.5	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =2A	-	3.6	4.5	Ω
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =V _{DSS} , V _{GS} =0V	-	-	10	uA
I _{GSS}	Gate to Source Leakage Current	V _{GS} =V _{GSS} , V _{DS} =0V	-	-	±100	nA

D-S Diode Characteristics and Maximum Rating @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Maximum Drain to Source Diode Forward Current		-	-	4.0	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0V, I _S =4A	-	0.9	1.2	V
T _{rr}	Reverse Recovery Time	V _{GS} =0V, I _S =4A,	-	550	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt=-100A/us	-	3.5	-	nC

Switching Characteristics @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t _{d(on)}	Turn-on Delay Time	I _D =4A, V _{DD} =750V, R _G =5Ω (Note 3)	-	30	-	ns
t _r	Rise Time		-	35	-	ns
t _{d(off)}	Turn-off Delay Time		-	50	-	ns
t _f	Fall Time		-	40	-	ns
C _{ies}	Input Capacitance	V _{GS} =0V, V _{DS} =25V, f=1.0MHz	-	1950	-	pF
C _{oes}	Output Capacitance		-	125	-	pF
C _{rss}	Reverse Transfer Capacitance		-	4.4	-	pF
Q _g	Total Gate Charge	I _D =4A, V _{DD} =600V V _{GS} =10V (Note 3)	-	45	-	nC
Q _{gs}	Gate to Source Charge		-	12	-	nC
Q _{gd}	Gate to Drain Charge		-	19	-	nC

Note:

1. Repetitive rating: pulse-width limited by maximum junction temperature
2. V_{DD}=100V, L=20mH, R_G=25Ω, V_G=10V, stating T_J=25°C
3. Essentially independent of operating temperature typical characteristics

Typical Performance Characteristics

Fig. 1. Typical on-Region Characteristics




Fig. 2. Typical Transfer Characteristics




Fig. 3. Static on-Resistance vs. I_D




Fig. 4. Body Diode Forward Voltage vs. I_{DR}




Fig. 5. Capacitance Characteristics





Fig. 6. Gate Charge Characteristics



Typical Performance Characteristics

Fig. 7. Breakdown Voltage vs. Temperature




Fig. 8. Static on-Resistance vs. Temperature




Fig. 9. Maximum Safe Operating Area




Fig. 10. Maximum Drain Current vs. Temperature






Fig. 11. Transient Thermal Response Curve



Package Dimensions

TO-3P

(Dimensions in Millimeters)



DISCLAIMER:

The products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any product can reasonably be expected to result in a personal injury. Seller's customers using or selling seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Sunnychip reserves the right to change the specifications and circuitry without notice at any time. Sunnychip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Sunnychip product.  is a registered trademark of Sunnychip Semiconductor Co., Ltd.