

SQA8N100

1000V 8A N-Channel Enhancement Mode Power MOSFET



Features

- Low on-Resistance: $R_{DS(on)}=1.135\Omega(\text{typ.})$
- Special Process Technology for high ESD Capability
- 100% Avalanche Test
- Good Stability and Uniformity with High E_{AS}

Applications

- UPS Applications
- DC-DC Converters and AC-DC Power Supply

Package Type & Internal Circuit



Absolute Maximum Ratings @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter		Ratings	Unit
V_{DSS}	Drain to Source Voltage		1000	V
V_{GSS}	Gate to Source Voltage		± 30	V
I_D	Drain Current	$T_C=25^\circ\text{C}$	8	A
		$T_C=100^\circ\text{C}$	5	A
I_{DM}	Pulsed Drain Current	(Note1)	32	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	225	W
	Derate above 25°C		1.78	W/ $^\circ\text{C}$
E_{AS}	Single Pulsed Avalanche Energy	(Note 2)	890	mJ
T_J	Operating Junction Temperature Range		-55~+150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-55~+150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	0.55	$^\circ\text{C}/\text{W}$
$R_{th(J-A)}$	Thermal Resistance, Junction to Ambient	40	$^\circ\text{C}/\text{W}$

Electrical Characteristics @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain to Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$	1000	-	-	V
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_D=250\mu\text{A}$	3.0	4.085	5	V
$R_{\text{DS(on)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}, I_D=4\text{A}$	-	1.135	-	Ω
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=1000\text{V}, V_{\text{GS}}=0\text{V}$	-	-	10	μA
I_{GSS}	Gate to Source Leakage Current	$V_{\text{GS}}=\pm 30\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 100	nA

D-S Diode Characteristics and Maximum Rating @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Maximum Drain to Source Diode Forward Current		-	-	8	A
V_{SD}	Drain-Source Diode Forward Voltage	$V_{\text{GS}}=0\text{V}, I_S=8\text{A}$	-	0.838	-	V
t_{rr}	Reverse Recovery Time		-	0.6	-	us
Q_{rr}	Reverse Recovery Charge	$V_{\text{GS}}=0\text{V}, I_S=8\text{A}, \frac{dI}{dt}=-100\text{A}/\text{us}$	-	5.1	-	μC

Switching Characteristics @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$t_{\text{d(on)}}$	Turn-on Delay Time	$I_D=8\text{A}, V_{\text{DD}}=500\text{V}, R_G=25\Omega$ (Note 3)	-	48	109	ns
t_r	Rising Time		-	95	198	ns
$t_{\text{d(off)}}$	Turn-off Delay Time		-	123	252	ns
t_f	Falling Time		-	77	168	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1.0\text{MHz}$	-	-	3200	pF
C_{oss}	Output Capacitance		-	-	255	pF
C_{rss}	Reverse Transfer Capacitance		-	-	23	pF
Q_g	Total Gate Charge	$I_D=8\text{A}, V_{\text{DS}}=800\text{V}$ $V_{\text{GS}}=10\text{V}$ (Note 3)	-	53	-	nC
Q_{gs}	Gate to Source Charge		-	12	-	nC
Q_{gd}	Gate to Drain Charge		-	24	-	nC

Note:

- Repetitive rating: pulse-width limited by maximum junction temperature
- $L=5\text{mH}, V_{\text{DD}}=100\text{V}, V_{\text{G}}=10\text{V}, @T_C=25^\circ\text{C}$
- Essentially independent of operating temperature typical characteristics

Typical Performance Characteristics

Fig. 1. Typical on-Region Characteristics




Fig. 3. Static on-Resistance vs. I_D




Fig. 5. Capacitance Characteristics




Fig. 2. Typical Transfer Characteristics




Fig. 4. Body Diode Forward Voltage vs. I_{DR}





Fig. 6. Gate Charge Characteristics



Typical Performance Characteristics

Fig. 7. Breakdown Voltage vs. Temperature




Fig. 8. Static on-Resistance vs. Temperature




Fig. 9. Maximum Safe Operating Area




Fig. 10. Maximum Drain Current vs. Temperature





Fig. 11. Transient Thermal Response Curve



Package Dimensions

TO-3PN

(Dimensions in Millimeters)

