

# SCH2065S4

## 20A, 650V SiC Schottky Barrier Diode

### Features

- Low Forward Voltage Drop:  $V_F=1.3V$  (typical @  $I_F=20A$ )
- Reverse Voltage:  $V_{RRM}=650V$
- Avalanche Energy Rated
- High Surge Capability
- Low Power Loss and High Efficiency
- Silicon Carbide Substrate

### Description

The SCH2065S4 is a SiC schottky barrier diode. It is base on silicon carbide material, and its switching behavior is independent with temperature. The device has superfast recovery property and lower forward voltage drop, it can be used in switching power supply, solar inverter, PFC and UPS.

### Applications

- Switching Power Supply
- Solar Inverter
- Power Factor Correction
- Uninterruptible Power Supply

### Package Type & internal Circuit



1. Cathode 2.Anode

### Absolute Maximum Ratings

per diode at  $T_C=25^\circ C$  unless otherwise noted

Symbol	Parameter		Ratings	Unit
$V_{RRM}$	Peak Repetitive Reverse Voltage		650	V
$V_{RWM}$	Working Peak Reverse Voltage		650	V
$V_R$	DC Blocking Voltage		650	V
$I_{F(AV)}$	Average Rectified Forward Current	per diode at $T_C=125^\circ C$	20	A
$I_{FSM}$	Non-repetitive Peak Surge Current	$t_p=10ms$ , half sine wave	120	A
		$t_p=200\mu s$ , square wave	480	A
$P_D$	Power Dissipation		183	W
$T_J$	Operating Junction Temperature Range		-55~+175	°C
$T_{STG}$	Storage Temperature Range		-55~+175	°C

### Thermal Characteristics

Symbol	Parameter	Ratings	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	0.82	°C/W


**Electrical Characteristics** per diode at  $T_C=25\text{ }^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$V_F$	Forward Voltage Drop	$I_F=20\text{A}$	-	1.3	1.5	V
		$I_F=20\text{A}, T_C=125\text{ }^\circ\text{C}$	-	1.4	1.7	V
$I_R$	Reverse Leakage Current	$V_R=650\text{V}$	-	-	200	uA
C	Total Capacitance	$V_R=0\text{V}, f=1\text{MHz}$	-	1210	-	pF
		$V_R=200\text{V}, f=1\text{MHz}$	-	124	-	
		$V_R=400\text{V}, f=1\text{MHz}$	-	90	-	
$Q_C$	Total Capacitive Charge	$V_R=400\text{V}, I_F=20\text{A}, dI/dt=-200\text{A/us}$	-	41	-	nC

## Package Dimensions

**TO-247**

(Dimensions in Millimeters)

**DISCLAIMER:**

The products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any product can reasonably be expected to result in a personal injury. Seller's customers using or selling seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Sunnychip reserves the right to change the specifications and circuitry without notice at any time. Sunnychip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Sunnychip product.  is a registered trademark of Sunnychip Semiconductor Co., Ltd.