

SCQH1000N170

1700V 1Ω N-Channel SiC Power MOSFET

Features

- Typical on-Resistance: $R_{DS(on)}=1\Omega(\text{typ.})$
- High Blocking Voltage
- 100% Avalanche Test
- Good Stability and Uniformity with High E_{AS}


Description

The SCQH1000N170 is a high blocking voltage N-Channel SiC power MOSFET. This device provide excellent performance for high voltage power supplies or pulse circuits.


Applications

- Solar Inverters
- High Voltage DC/DC Converters
- Motor Drivers
- Switch Mode Power Supplies

Package Type & Internal Circuit



TO-247



Absolute Maximum Ratings @ $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter		Ratings	Unit
V_{DSS}	Drain to Source Voltage		1700	V
V_{GSS}	Gate to Source Voltage		-10/+25	V
V_{GSop}	Recommended operation Values of Gate -Source Voltage		-5/+20	V
I_D	Drain Current	$T_c=25^\circ\text{C}$	5.0	A
		$T_c=100^\circ\text{C}$	3.0	A
I_{DM}	Pulsed Drain Current	(Note1)	20.0	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	62	W
	Derate above 25°C		0.5	W/°C
T_J	Operating Junction Temperature Range		-55~+150	°C
T_{STG}	Storage Temperature Range		-55~+150	°C

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	2.02	°C/W
$R_{th(J-A)}$	Thermal Resistance, Junction to Ambient	40	°C/W

Electrical Characteristics @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain to Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=100\mu\text{A}$	1700	-	-	V
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=1\text{mA}$	2.0	2.6	4.0	V
$R_{\text{DS(on)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=20\text{V}, I_{\text{D}}=2\text{A}$	-	1	1.3	Ω
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=V_{\text{DSS}}, V_{\text{GS}}=0\text{V}$	-	-	100	μA
I_{GSS}	Gate to Source Leakage Current	$V_{\text{GS}}=V_{\text{GSS}}, V_{\text{DS}}=0\text{V}$	-	-	± 250	nA

D-S Diode Characteristics and Maximum Rating @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{SD}	Drain-Source Diode Forward Voltage	$V_{\text{GS}}=-5\text{V}, I_{\text{S}}=1\text{A}$	-	4.2	-	V
t_{rr}	Reverse Recovery Time	$V_{\text{GS}}=0\text{V}, I_{\text{S}}=2\text{A},$ $dI/dt=-290\text{A}/\mu\text{s}$	-	25	-	ns
Q_{rr}	Reverse Recovery Charge		-	15	-	nC

Switching Characteristics @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$t_{\text{d(on)}}$	Turn-on Delay Time	$I_{\text{D}}=30\text{A},$ $V_{\text{DD}}=1200\text{V},$ $R_{\text{G}}=2.5\Omega$ $V_{\text{GS}} = -5/20\text{V},$ (Note 3)	-	5	-	ns
t_r	Turn-on Rise Time		-	9.2	-	ns
$t_{\text{d(off)}}$	Turn-off Delay Time		-	13.8	-	ns
t_f	Turn-off Fall Time		-	22.8	-	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=1000\text{V},$ $f=1.0\text{MHz}$	-	194	-	pF
C_{oss}	Output Capacitance		-	13	-	pF
C_{rss}	Reverse Transfer Capacitance		-	1.8	-	pF
Q_g	Total Gate Charge	$I_{\text{D}}=2\text{A},$ $V_{\text{DD}}=1200\text{V}$ $V_{\text{GS}}=-5/20\text{V}$ (Note 3)	-	23	-	nC
Q_{gs}	Gate to Source Charge		-	5.4	-	nC
Q_{gd}	Gate to Drain Charge		-	7.6	-	nC


Note:

1. Repetitive rating: pulse-width limited by maximum junction temperature
2. $V_{\text{DD}}=100\text{V}, L=1\text{mH}, V_{\text{G}}=10\text{V}, I_{\text{D}}=2.0\text{A}$
3. Essentially independent of operating temperature typical characteristics

Package Dimensions

TO-247

(Dimensions in Millimeters)



DISCLAIMER:

The products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any product can reasonably be expected to result in a personal injury. Seller's customers using or selling seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Sunnychip reserves the right to change the specifications and circuitry without notice at any time. Sunnychip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Sunnychip product. S+S® is a registered trademark of Sunnychip Semiconductor Co., Ltd.